

SWIVEL CASTOR FOR BASE AND UPPER SIDE

3470 PVR 080 P62

Wheel diameter	80 mm	3,15 "
Tread width	35 mm	1,38 "
Plate dimensions	105 x 85 mm	4,14 x 3,35 "
Bolt hole pattern on plate	80 / 77x 60 mm	3,15 / 3,03 x 2,36 "
Plate hole	9 mm	0,35 "
Offset	44,5 mm	1,75 "
Swivel interference-Ø	169 mm	6,65 "
Dynamic load capacity	70 Kg / daN	150 LBS
Static load capacity	175 Kg / daN	385 LBS
Weight	0,779 Kg / daN	1,717 LBS
Temperature resistant area	- 20 / + 60 °C	- 4 / + 140 °F
Norms	EN 12532	EN 12532
Construction height	108 mm	4,25 "



Description

Swivel Caster, housing made of zinc-chromatised pressed steel, double ball bearing swivel head, dustguard, wheel axle with nut, black wheel made of Polypropylene, tread made of black rubber, roller bearing, plate fitting.

SWIVEL CASTOR FOR BASE WITH BRAKE

3477 PVR 080 P62

Wheel diameter	80 mm	3,15 "
Tread width	35 mm	1,38 "
Plate dimensions	105 x 85 mm	4,14 x 3,35 "
Bolt hole pattern on plate	80 / 77x 60 mm	3,15 / 3,03 x 2,36 "
Plate hole	9 mm	0,35 "
Offset	44,5 mm	1,75 "
Swivel interference-Ø	246 mm	9,69 "
Dynamic load capacity	70 Kg / daN	150 LBS
Static load capacity	175 Kg / daN	385 LBS
Weight	0,952 Kg / daN	2,099 LBS
Temperature resistant area	- 20 / + 60 °C	- 4 / + 140 °F
Norms	EN 12532	EN 12532
Construction height	108 mm	4,25 "



Description

Swivel Caster, with total lock, tail end of castor, housing made of zinc-chromatised pressed steel, double ball bearing swivel head, dustguard, wheel axle with nut, black wheel made of Polypropylene, tread made of black rubber, roller bearing, plate fitting.

FIXED CASTOR FOR LOWER SIDE

3478 DVR 100 P62

Wheel diameter	100 mm	4 "
Tread width	30 mm	1,18 "
Plate dimensions	103 x 85 mm	4,06 x 3,35 "
Bolt hole pattern on plate	80 / 77x 60 mm	3,15 / 3,03 x 2,36 "
Plate hole	9 mm	0,35 "
Dynamic load capacity	70 Kg / daN	150 LBS
Static load capacity	175 Kg / daN	385 LBS
Weight	0,69 Kg / daN	1,521 LBS
Temperature resistant area	- 20 / + 60 °C	- 4 / + 140 °F
Norms	EN 12532	EN 12532
Construction height	128 mm	5,04 "



Description

Rigid Caster, housing made of zinc-chromatised pressed steel, wheel axle with nut, wheel center made of zinc-chromatised steel mit black tread made of rubber, maintenance-free roller bearing, threadguards, plate fitting.